## Wind Mitigation Report

LOCATED AT: 1865 Bay Road Vero Beach, Florida 32963

PREPARED EXCLUSIVELY FOR: Spinnaker Point Condominium

INSPECTED ON: Tuesday, September 12, 2023

Inspector, Simon Skarbelis HI 13536 Simon Home Inspections, LLC

## **Uniform Mitigation Verification Inspection Form**

Maintain a copy of this form and any documentation provided with the insurance policy

| Inspection Date: <b>09/12/2023</b>  |   |                                  |   |  |  |  |  |
|---|---|----------------------------------|---|--|--|--|--|
| Owner Information   |   |                                  |   |  |  |  |  |
| Owner Name: Spinnaker Point Condominium Contact Person:   |   |                                  |   |  |  |  |  |
| Address: 1865 Bay Road Home Phone:  |   |                                  |   |  |  |  |  |
| City: Vero Beach  | Zip: <b>32963</b>   |                                  | Work Phone:                                     |  |  |  |  |
| County: Indian River  |   |                                  | Cell Phone:                                     |  |  |  |  |
| Insurance Company: Policy #:  |   |                                  |   |  |  |  |  |
| Year of Home: 1981  | # of Stories: 3   |                                  | Email: jonnas@elliott                           | merrill.com                                  |  |  |  |
| NOTE: Any documentation used in validating the compliance or existence of each construction or mitigation attribute must accompany this form. At least one photograph must accompany this form to validate each attribute marked in questions 3 though 7. The insurer may ask additional questions regarding the mitigated feature(s) verified on this form.  |   |                                  |   |  |  |  |  |
| the HVHZ (Miami-Dade or Broward cou   | <b>Building Code</b> : Was the structure built in compliance with the Florida Building Code (FBC 2001 or later) OR for homes located in the HVHZ (Miami-Dade or Broward counties), South Florida Building Code (SFBC-94)?   |                                  |   |  |  |  |  |
| ☐ A. Built in compliance with the FBC a date after 3/1/2002: Building Perm  |   |                                  |   | mit application with                         |  |  |  |
| ☐ B. For the HVHZ Only: Built in con provide a permit application with a control of the control |   |                                  |   |  |  |  |  |
| C. Unknown or does not meet the re  | quirements of Answer  | "A" or "B"                       |   |  |  |  |  |
| 2. <b>Roof Covering:</b> Select all roof covering OR Year of Original Installation/Replace covering identified.   |   |                                  |   |  |  |  |  |
| Permit  | Application<br>Date   | FBC or MDC<br>Product Approval # | Year of Original Installation or<br>Replacement | No Information<br>Provided for<br>Compliance |  |  |  |
| ▼ 1. Asphalt/Fiberglass Shingle  2. Asphalt/Fiberglass Shingle  3. Asphalt/Fiberglass Shingle  3. Asphalt/Fiberglass Shingle  3. Asphalt/Fiberglass Sh     | 6/14  | 2014060200                       | 2014  |  |  |  |  |
| 2. Concrete/Clay Tile   |   |                                  |   |  |  |  |  |
|   |   |                                  |   |  |  |  |  |
|   | /   |                                  |   |  |  |  |  |
|   |   |                                  |   |  |  |  |  |
| П   | /   |                                  |   |  |  |  |  |
|   |   |                                  |   |  |  |  |  |
|   | B. All roof coverings have a Miami-Dade Product Approval listing current at time of installation OR (for the HVHZ only) a roofing permit application after 9/1/1994 and before 3/1/2002 OR the roof is original and built in 1997 or later.   |                                  |   |  |  |  |  |
| ☐ C. One or more roof coverings do no   | ot meet the requiremen  | ts of Answer "A" or              | "B".  |  |  |  |  |
| ☐ D. No roof coverings meet the requi   | rements of Answer "A  | " or "B".                        |   |  |  |  |  |
| 3. <b>Roof Deck Attachment</b> : What is the we   | akest form of roof dec  | k attachment?                    |   |  |  |  |  |
| by staples or 6d nails spaced at 6" a shinglesOR- Any system of screw   | A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the fieldOR- Batten decking supporting wood shakes or wood shinglesOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift less than that required for Options B or C below. |                                  |   |  |  |  |  |
| 24"inches o.c.) by 8d common nails other deck fastening system or truss.  |   |                                  |   |  |  |  |  |
| 24"inches o.c.) by 8d common nails decking with a minimum of 2 nails and Any system of screws, nails, adhesi  | 24"inches o.c.) by 8d common nails spaced a maximum of 6" inches in the fieldOR- Dimensional lumber/Tongue & Groove decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in width)OR-Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent  |                                  |   |  |  |  |  |
| Inspectors Initials SS Property Address 1865 Bay Road Vero Beach, Florida 32963   |   |                                  |   |  |  |  |  |

\*This verification form is valid for up to five (5) years provided no material changes have been made to the structure. OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155

Page 2 of 11

|    |      | or greater res         | istance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least   |
|----|------|------------------------|--|
|    | П    | •                      | ed Concrete Roof Deck.   |
|    | П    |                        |  |
|    | П    |                        | or unidentified.   |
|    |      | G. No attic a          |  |
|    |      |                        |  |
| 4. |      | eet of the insid       | tachment: What is the <u>WEAKEST</u> roof to wall connection? (Do not include attachment of hip/valley jacks within e or outside corner of the roof in determination of WEAKEST type)  |
|    |      | A. Toe Nails           |  |
|    |      |                        | Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or   |
|    |      |                        | Metal connectors that do not meet the minimal conditions or requirements of B, C, or D   |
|    | Miı  | nimal conditio         | ons to qualify for categories B, C, or D. All visible metal connectors are:  |
|    |      | X                      | Secured to truss/rafter with a minimum of three (3) nails, and   |
|    |      | X                      | Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter <b>and</b> blocked no more than 1.5" of the truss/rafter, <b>and</b> free of visible severe corrosion.   |
|    | X    | B. Clips               |  |
|    |      | X                      | Metal connectors that do not wrap over the top of the truss/rafter, <b>or</b>  |
|    |      |                        | Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails.   |
|    |      | C. Single W            | raps   |
|    |      |                        | Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.   |
|    |      | D. Double V            | Vraps  |
|    |      |                        | Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, <b>or</b> |
|    |      |                        | Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side.   |
|    |      | E. Structural          | Anchor bolts structurally connected or reinforced concrete roof.   |
|    |      | F. Other:              |  |
|    |      | G. Unknown             | or unidentified  |
|    |      | H. No attic a          | access   |
|    |      |                        |  |
| 5. |      |                        | What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).   |
|    |      | A. Hip Roof            | Hip roof with no other roof shapes greater than 10% of the total roof system perimeter.  Total length of non-hip features: feet; Total roof system perimeter: feet   |
|    |      | B. Flat Roof           | · · · · · · · · · · · · · · · · · · ·  |
|    | X    | C. Other Roo           |  |
| 6  | Sec  | ondary Wate            | er Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR)   |
| 0. | X    | A. SWR (also sheathing | so called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the   |
|    | П    | B. No SWR.             | from water intrusion in the event of roof covering loss.   |
|    |      |                        | or undetermined.   |
| In | spec | tors Initials _        | SS_Property Address_1865 Bay Road Vero Beach, Florida 32963  |
|    |      |                        |  |

\*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

7. **Opening Protection:** What is the **weakest** form of wind borne debris protection installed on the structure? **First**, use the table to determine the weakest form of protection for each category of opening. Second, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings and (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable.

| Opening Protection Level Chart  Place an "X" in each row to identify all forms of protection in use for each opening type. Check only one answer below (A thru X), based on the weakest form of protection (lowest row) for any of the Glazed openings and indicate the weakest form of protection (lowest row) for Non-Glazed openings. |   | Glazed Openings              |                 |           |                | Non-Glazed<br>Openings |                 |
|--|---|------------------------------|-----------------|-----------|----------------|------------------------|-----------------|
|  |   | Windows<br>or Entry<br>Doors | Garage<br>Doors | Skylights | Glass<br>Block | Entry<br>Doors         | Garage<br>Doors |
| N/A  | Not Applicable- there are no openings of this type on the structure   |                              | x               |           | X              |                        |                 |
| Α  | Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights)  |                              |                 |           |                |                        |                 |
| В  | Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights)  |                              |                 |           |                |                        |                 |
| С  | Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007   |                              |                 |           |                |                        |                 |
| D  | Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance |                              |                 |           |                |                        |                 |
| N  | Opening Protection products that appear to be A or B but are not verified   |                              |                 |           |                |                        |                 |
| IN   | Other protective coverings that cannot be identified as A, B, or C  |                              |                 |           |                |                        |                 |
| Х  | No Windborne Debris Protection  | Х                            |                 | X         |                | x                      | Х               |

| A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at  |
|---|
| a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval |
| system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure    |
| and Large Missile Impact" (Level A in the table above).   |

- Miami-Dade County PA 201, 202, and 203
- Florida Building Code Testing Application Standard (TAS) 201, 202, and 203

A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist

- American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996
- Southern Standards Technical Document (SSTD) 12
- For Skylights Only: ASTM E 1886 and ASTM E 1996
- For Garage Doors Only: ANSI/DASMA 115

|  | X in the table above  |  |  |  |
|--|---|--|--|--|
|  | ☐ A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above   |  |  |  |
| B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the for "Cyclic Pressure and Large Missile Impact" (Level B in the table above): |   |  |  |  |
|  | • ASTM E 1886 and ASTM E 1996 (Large Missile – 4.5 lb.)   |  |  |  |
|  | • SSTD 12 (Large Missile – 4 lb. to 8 lb.)  |  |  |  |
|  | • For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile - 2 to 4.5 lb.)  |  |  |  |
|  | B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist                                      |  |  |  |
|  | ☐ B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X |  |  |  |

A.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or

☐ C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007 All Glazed openings are covered with plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above).

C.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist

C.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in the table above

☐ C.3 One or More Non-Glazed openings is classified as Level N or X in the table above

B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above

Inspectors Initials SS Property Address 1865 Bay Road Vero Beach, Florida 32963

in the table above

<sup>\*</sup>This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

| N. Exterior Opening Protection (unverified shutter s protective coverings not meeting the requirements of Ar with no documentation of compliance (Level N in the ta   | nswer "A", "B", or C" or syst   |           |                                   |  |  |
|---|---|-----------|-----------------------------------|--|--|
| N.1 All Non-Glazed openings classified as Level A, B, C, or N in the table above, or no Non-Glazed openings exist   |   |           |                                   |  |  |
| N.2 One or More Non-Glazed openings classified as Level table above   | N.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level X in the |           |                                   |  |  |
| ☐ N.3 One or More Non-Glazed openings is classified as Leve   | el X in the table above   |           |                                   |  |  |
| X. None or Some Glazed Openings One or more Glaze   | ed openings classified and Le   | evel X in | the table above.                  |  |  |
| MITIGATION INSPECTIONS MUST B<br>Section 627.711(2), Florida Statutes, provi  | ides a listing of individuals w   | vho may   |                                   |  |  |
| Qualified Inspector Name: Simon Skarbelis   | License Type: Home Inspec   | tor       | License or Certificate #: HI13536 |  |  |
| Inspection Company: Simon Home Inspections, LLC   |   | Phone: 32 | 21.759.3350                       |  |  |
| Qualified Inspector – I hold an active license as a   | : (check one)   |           |                                   |  |  |
| Home inspector licensed under Section 468.8314, Florida Statutes who has completed the statutory number of hours of hurricane mitigation training approved by the Construction Industry Licensing Board and completion of a proficiency exam.  Building code inspector certified under Section 468.607, Florida Statutes.  General, building or residential contractor licensed under Section 489.111, Florida Statutes.  Professional engineer licensed under Section 471.015, Florida Statutes.  Professional architect licensed under Section 481.213, Florida Statutes.  Any other individual or entity recognized by the insurer as possessing the necessary qualifications to properly complete a uniform mitigation verification form pursuant to Section 627.711(2), Florida Statutes.  Individuals other than licensed contractors licensed under Section 489.111, Florida Statutes, or professional engineer licensed |   |           |                                   |  |  |
| Licensees under s.471.015 or s.489.111 may authorize a direct employee who possesses the requisite skill, knowledge, and experience to conduct a mitigation verification inspection.  I, Simon Skarbelis am a qualified inspector and I personally performed the inspection or (licensed (print name))  contractors and professional engineers only) I had my employee (print name of inspector)  and I agree to be responsible for his/her work.  Qualified Inspector Signature:  Date: 09/12/2023   |   |           |                                   |  |  |
| An individual or entity who knowingly or through gross negligence provides a false or fraudulent mitigation verification form is subject to investigation by the Florida Division of Insurance Fraud and may be subject to administrative action by the appropriate licensing agency or to criminal prosecution. (Section 627.711(4)-(7), Florida Statutes) The Qualified Inspector who certifies this form shall be directly liable for the misconduct of employees as if the authorized mitigation inspector personally performed the inspection.   |   |           |                                   |  |  |
| <u>Homeowner to complete</u> : I certify that the named Qualified Inspector or his or her employee did perform an inspection of the residence identified on this form and that proof of identification was provided to me or my Authorized Representative.  |   |           |                                   |  |  |
| Signature: Date:  |   |           |                                   |  |  |
| An individual or entity who knowingly provides or utters a obtain or receive a discount on an insurance premium to w of the first degree. (Section 627.711(7), Florida Statutes)  |   |           |                                   |  |  |
| The definitions on this form are for inspection purposes only and cannot be used to certify any product or construction feature as offering protection from hurricanes.   |   |           |                                   |  |  |
| Inspectors Initials SS Property Address 1865 Bay Road Vero Beach, Florida 32963   |   |           |                                   |  |  |
| *This verification form is valid for up to five (5) years proving curacies found on the form  | ided no material changes h  | ave bee   | n made to the structure or        |  |  |

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155

Page 5 of 11

## **Photos**


## **Photos**



Elevation and unprotected glazed openings



Elevation and unprotected glazed openings





Elevation and unprotected glazed openings



Elevation and unprotected glazed openings



Elevation and unprotected glazed openings



Elevation and unprotected glazed openings



Elevation and unprotected glazed openings



Elevation and unprotected glazed openings



Elevation and unprotected glazed openings



Elevation and unprotected glazed openings



Elevation and unprotected glazed openings



Elevation and unprotected glazed openings



Elevation and unprotected glazed openings



Elevation and unprotected glazed openings




Elevation and unprotected glazed openings



Elevation and unprotected glazed openings



Unprotected glazed opening skylight




Unprotected garage doors





Unprotected garage doors



Clips







The Spinnaker Point Condominium Report 1865 Bay Road Vero Beach, Florida 32963 Tuesday, September 12, 2023







Roof

Roof

Roof







Roof

Roof

Roof





Roof

Roof